

The Standard of Excellence in Ultraviolet Manufacturers / Engineers / Sales / Service Germicidal Ultraviolet – Equipment & Lamps

MEGATRON® Model M50

- Flow Rates: 70 GPM / Clear Wastewater
 - 90 GPM / Clear Fresh Water
 - 100 GPM / High Purity Water
- Construction: Type 316 Stainless Steel Electropolished & Passivated
 - 5 1/2" Diameter Chamber with 2" NPT Inlet and Outlet
 - (4) G64T5L Ultraviolet Germicidal Lamps
 - NEMA type Electrical Enclosure

Features:

- Digital Ultraviolet Monitor with Outputs
 - Status Display Window
 - Elapsed Time Indicator
 - Individual Lamp Operational Indicators
 - Two Drain Fittings
 - Two Sight Port Fittings
 - Test Ports on Inlet & Outlet
 - Modular Design
 - Plug-In Components
 - State of the Art Electronic Ballasts
 - Removable Flanged Heads
 - Fused Quartz Sleeves
- **Options:** Patented Automatic Programmable Wiper
 - Patented Manual Wiper
 - 3" Lap Joint Flange (Inlet / Outlet)
 - Ultraviolet Face Shield

375 Marcus Boulevard Hauppauge, NY 11788 Tel: (631) 273-0500 Fax: (631) 273-0771 Shop: <u>AtlanticUltraviolet.com</u> Learn More: <u>Ultraviolet.com</u> Email: Sales@AtlanticUV.com