

# GUARDIAN™

## Ultraviolet Monitor Comparison

### FEATURES

Key: | \* Some Restrictions | ✓ = Yes



Model	Digital Direct Mount Monitor			Digital Direct Mount Monitor Kit		Digital Remote Mount Monitor		
Available Voltages	110/220v or 12v DC			110/220v		110/220v or 12v DC		
Installation	Mounted directly to the water purifier using a standard probe that is installed into the sight port fitting. The collar on the bottom of the monitor is secured over the sensor probe.			Two Digital Direct Mount monitors, one for each chamber. Each reads the UV levels independently, but they work together to shut down flow if UV falls below its trip point.		Intended for use in locations away from the water purifier. The remote probe installs into the sight port fitting of the water purifier. The remote probe cable connects the probe to the monitor.		
<b>GUARDIAN™ UV Models</b>	<b>30-8251</b> 110/220v	<b>30-8250</b> 110/220v	<b>30-8255</b> 12v	<b>30-8249</b> ① 110/220v		<b>30-8253</b> 110/220v	<b>30-8252</b> 110/220v	<b>30-8257</b> 12v
All <b>MIGHTY★PURE®</b> Models	✓	—	✓	—		✓	—	✓
<b>SANITRON® S17A</b>	✓	—	✓	—		✓	—	✓
<b>SANITRON® S23A</b>	✓	—	✓	—		✓	—	✓
<b>SANITRON® S37C</b>	✓	—	✓	—		✓	—	✓
<b>SANITRON® S50C</b>	✓	—	✓	—		✓	—	✓
<b>SANITRON® S2400C &amp; Up</b>	—	✓	—	—		—	✓	—
<b>SANITRON® S5,000C</b>	—	✓	—	✓		—	✓	—
What's Included?	<ul style="list-style-type: none"> <li>• <b>GUARDIAN™</b> Monitor</li> <li>• Standard Probe</li> <li>• 110/220v or 12v Power Adapter</li> <li>• Manual (98-1715)</li> <li>• Internal Audio Alarm</li> <li>• Internal Time Delay</li> </ul>			<ul style="list-style-type: none"> <li>• <b>GUARDIAN™</b> Monitors (2)</li> <li>• Standard Probe (2)</li> <li>• Series Power Cable (3ft)</li> <li>• 110/220v or 12v Power Adapter</li> <li>• Manual (98-1715)</li> <li>• Internal Audio Alarm</li> <li>• Internal Time Delay</li> </ul>		<ul style="list-style-type: none"> <li>• <b>GUARDIAN™</b> Monitor</li> <li>• Remote Probe</li> <li>• Remote Cable</li> <li>• 110/220v or 12v Power Adapter</li> <li>• Manual (98-1715)</li> <li>• Internal Audio Alarm</li> <li>• Internal Time Delay</li> </ul>		
Optional Accessories	<ul style="list-style-type: none"> <li>• RJ45 Modular Cable*</li> <li>• RJ45 Modular Jack Adapter*</li> <li>• <b>Promate™</b> Solenoid Valve</li> <li>• <b>Promate™</b> Remote Audio Alarm</li> <li>• Reducing Bushing for Probe</li> </ul>			<ul style="list-style-type: none"> <li>• RJ45 Modular Cable*</li> <li>• RJ45 Modular Jack Adapter*</li> <li>• <b>Promate™</b> Solenoid Valve</li> <li>• <b>Promate™</b> Remote Audio Alarm</li> <li>• Series Power Cable (6 ft)</li> <li>• Reducing Bushing for Probe</li> </ul>		<ul style="list-style-type: none"> <li>• RJ45 Modular Cable*</li> <li>• RJ45 Modular Jack Adapter*</li> <li>• <b>Promate™</b> Solenoid Valve</li> <li>• <b>Promate™</b> Remote Audio Alarm</li> <li>• Reducing Bushing for Probe</li> <li>• Female to Male Extender Cable</li> </ul>		

① Dual Digital **GUARDIAN™** Ultraviolet Monitor Kit is available for the **SANITRON® S5,000C**

\* An RJ45 modular cable is required to interconnect between the **GUARDIAN™** Ultraviolet Monitor and other remote monitoring devices. An RJ45 modular jack adapter might be needed to interconnect the RJ45 cable and a remote monitoring device. The RJ45 modular jack adapter and the RJ45 modular cable are not included with the purchase of the **GUARDIAN™** Ultraviolet Monitor and if required, may be purchased separately.



375 Marcus Boulevard  
Hauppauge, NY 11788  
631.273.0500 • Fax: 631.273.0771  
Email: Sales@AtlanticUV.com  
Ultraviolet.com • BuyUltraviolet.com

