

Specifications

Model Number:	10-0038C-R
Input Voltage:	100v AC
Frequency:	50/60 Hz.
Lamp Type	See Chart on Next Page
Certifications:	RoHS
Size:	6.25"(max) x 2.5" x 1.75"
Weight:	11 oz.
Mounting:	Slotted Mounting Tabs



1. Ground case in accordance with the National Electric Code.
2. Remote mounting distance varies with lamp type, consult factory with requirements.



The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation® and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.

Lamp Types

Lamps	Wiring Diagrams
MIGHTY★PURE [®] MP16A, SANITRON [®] S17A Lamp Part No. 05-1098-R	2
MIGHTY★PURE [®] MP22A, SANITRON [®] S23A Lamp Part No. 05-1097-R	2
MIGHTY★PURE [®] MP36C, SANITRON [®] S37C Lamp Part No. 05-1343-R	1
MIGHTY★PURE [®] MP49C, SANITRON [®] S50C Lamp Part No. 05-1334-R	1
G12 – G48T5	1
GPH212 – GPH1148T5	2

This ballast may be acceptable for use with lamps not listed here.
Contact us to discuss your requirement.

Connections




Figure 1- Typical Connections from Ballast for use with Instant Lamps




Figure 2- Typical Connections from Ballast for use with Preheat Lamps

The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation[®] and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.