

Specifications

Voltage:	120 - 230 volts (+ or - 10%) AC 50 or 60 Hz
Operating Current:	10 milliamps
Tone Frequency:	2.8 kHz + /- 0.5 kHz.
Pulse Rate:	Approx. 1 per Second
Pulse Duration:	Approx. 1 per Second
Audio Output:	At least 110 dbs at 10 centimeters (4"),
Operating Temperature:	-20° C to +70° C. (-4° F to +158° F).
Enclosure:	Black ABS High impact resistant Plastic.
Size:	1.6"H x 2.0"W x 3.9" L. (4 x 5.1 x 9.9 cms)
Weight:	6 oz. (with cable & plug)
Mounting Centers:	3.5" (8.9 cms)
Power Plug:	2-pin NEMA
Cable Length:	36" approx.

The Audio Alarm emits a loud, pulsating beep when powered from an AC outlet (from 120v – 230v).

The Audio Alarm can be utilized in conjunction with the **GUARDIAN®** Monitor or **GUARDIAN®** Digital Monitor to alert when the lamp output is too low with the **SENTRY™** Safety Sensor to alert when the lamp fails.



The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation® and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.