



Specifications

Model Number:	10-0057C
Input Voltage:	24v DC
Frequency:	40 kHz.
Designed for:	Minipure® Water Purifiers Models MIN-1, MIN-1.5, MIN-3, MIN-6 and MIN-9 Biologic® BIO-1.5 and BIO-3
Size:	10.50" (Max) x 2.5" x 1.75"
Weight:	1 lb. 5 oz.
Mounting:	Slotted Mounting Tabs
Special Features:	LED to indicate lamp operation



The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation® and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.

Connections



Warnings

Many individuals regard ballasts and units powered by 12volt and 24volt Direct Current (DC) to be relatively benign from a safety standpoint. However, a DC ballast, in order to operate an ultraviolet discharge lamp, must produce an output as high as 600 volts. This voltage is high enough to produce a very serious or even lethal electric shock. IT IS IMPERATIVE that all DC ballasts and DC ultraviolet units be wired and grounded appropriately.

Note Warning Labels:

⚠ WARNING: The equipment that this ballast is utilized with **MUST** be grounded in accordance with local codes and the National Electrical Code. Failure to do so may result in serious personal injury. All wiring must be done by a qualified electrician. 00-0355

Failure to ground all Direct Current (DC) ballasts and/or the equipment it is employed in can result in serious injury or death.



⚠ WARNING: Disconnect Power before servicing or relamping.