

## 12v Solenoid Valves

Potable Water, 2-Way, Internally Piloted, Normally Closed

### Specifications

Sealing Material: EPDM/NSF

Medium: Potable Water

Ambient Temperature Range: 32–125° F ①

Model No.	Pipe Size NPT	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max Pressure (PSI) ②	Material	Certification	Voltage
27-3361	3/4"	6.7	8	8	150	Brass / Lead Free	NSF®/ANSI 61-G	12v*
27-3363	1"	13.00	8	8	150	Brass / Lead Free	NSF®/ANSI 61-G	12v*
27-3365	1-1/2"	30.00	8	8	150	Brass / Lead Free	NSF®/ANSI 61-G	12v*
27-3367	2"	48.00	8	8	150	Brass / Lead Free	NSF®/ANSI 61-G	12v*

① When used with our water purifiers, ambient temperature surrounding the water purifier should be between 35°F and 100°F.

② When used with our water purifiers, max recommended operating pressure is 100 PSI. Refer to the water purifier manual for more information.

Also available in Stainless Steel and Normally Open valves. Contact factory for specifics.

**Promate™**  
ACCESSORIES & REPLACEMENT PARTS



**3/4"**  
**12v\***  
27-3361

**Promate™**  
ACCESSORIES & REPLACEMENT PARTS



**1"**  
**12v\***  
27-3363

**Promate™**  
ACCESSORIES & REPLACEMENT PARTS



**1-1/2"**  
**12v\***  
27-3365

**Promate™**  
ACCESSORIES & REPLACEMENT PARTS



**2"**  
**12v\***  
27-3367

\*Designed to work with our Digital GUARDIAN™ Monitor models 30-8250, 30-8251, 30-8252, 30-8253, 30-8255, and 30-8257. Do NOT use 12v valves with any other GUARDIAN™ models.

The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation® and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.

375 Marcus Boulevard, Hauppauge, NY 11788 • USA • (631) 273-0500 • Fax: (631) 273-0771 • Email: Sales@AtlanticUV.com • AtlanticUltraviolet.com • Ultraviolet.com  
Document No. 98-1736 • August 2024 • ©2024 by Atlantic Ultraviolet Corporation®

## 120v Solenoid Valves

Potable Water, 2-Way, Internally Piloted, Normally Closed

### Specifications

Sealing Material: EPDM/NSF

Temperature Range: 32° – 125° F ①

Electrical Connection: Rating NEMA4

Medium: Potable Water

Model No.	Pipe Size NPT	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max Pressure (PSI) ②	Material	Certification	Voltage
27-3369	3/4"	6.7	8	8	150	Brass / Lead Free	NSF®/ANSI 61-G	120v 60Hz
27-3371	1"	13.00	8	8	150	Brass / Lead Free	NSF®/ANSI 61-G	120v 60Hz
27-3373	1-1/2"	30.00	8	8	200	Brass / Lead Free	NSF®/ANSI 61-G	120v 60Hz
27-3375	2"	48.00	8	8	200	Brass / Lead Free	NSF®/ANSI 61-G	120v 60Hz

① When used with our water purifiers, ambient temperature surrounding the water purifier should be between 35°F and 100°F.

② When used with our water purifiers, max recommended operating pressure is 100 PSI. Refer to the water purifier manual for more information.

Also available in Stainless Steel and Normally Open valves. Contact factory for specifics.



The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation® and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.

375 Marcus Boulevard, Hauppauge, NY 11788 • USA • (631) 273-0500 • Fax: (631) 273-0771 • Email: Sales@AtlanticUV.com • AtlanticUltraviolet.com • Ultraviolet.com  
Document No. 98-1736 • August 2024 • ©2024 by Atlantic Ultraviolet Corporation®